

# MARSHALL 1100 SERIES FURNACE

MODEL NUMBER	INTERNAL		EXTERNAL		FLAT ZONE @ 1000°C			TAPS	VOLTS	WATTS
	ID	LENGTH	OD	LENGTH	+/-6°C	+/-3°C	+/-1°C			
1113	1.5	11	10	14.5	7.5	6	4.5	6	110	750
1114	1.5	14.5	10	18	11	9.5	8	10	110	1000
1116	1.5	18.5	10	22	15	13.5	12	10	110	1230
1117	1.5	22.5	10	26	19	17.5	16	16	110	1640
1118	1.5	26.5	10	30	23	21.5	20	16	115	1810
1118A	1.5	30.5	10	34	27	25.5	24	16	115	2110
1119	1.5	34.5	10	38	31	29.5	28	18	220	2270
1123	2	11	10	14.5	6.5	4.5	2.3	8	110	1100
1124	2	14.5	10	18	10	8	6	10	110	1140
1126	2	18.5	10	22	14	12	10	12	110	1510
1127	2	22.5	10	26	18	16	14	16	110	1980
1128	2	26.5	10	30	22	20	18	14	115	2510
1128A	2	30.5	10	34	26	24	22	14	230	3030
1129	2	34.5	10	38	30	28	26	16	220	3160
1133	2.5	11	10	14.5	5.5	3	0.5	8	110	1520
1134	2.5	14.5	10	18	9	6.5	4	10	110	1550
1136	2.5	18.5	10	22	13	10.5	8	12	110	1980
1137	2.5	22.5	10	26	17	14.5	12	12	110	2725
1138	2.5	26.5	10	30	21	18.5	16	14	230	2890
1138A	2.5	30.5	10	34	25	22.5	20	14	220	3150
1139	2.5	34.5	10	38	29	26.5	24	16	220	3630
1143	3	11	10	14.5	4.5	1.5		6	110	1670
1144	3	14.5	10	18	8	5	2	10	110	1930
1146	3	18.5	10	22	12	9	6	12	220	2600
1147	3	22.5	10	26	16	13	10	10	220	2890
1148	3	26.5	10	30	20	17	14	16	230	3700
1148A	3	30.5	10	34	24	21	18	14	230	4180
1149	3	34.5	10	38	28	25	22	16	220	4730
1154	3.5	14.5	12	18	7	35		6	110	2600
1156	3.5	18.5	12	22	11	7.5	4	10	220	3100
1157	3.5	22.5	12	26	15	11.5	8	10	220	3960
1158	3.5	26.5	12	30	19	15.5	12	14	220	4220
1158A	3.5	30.5	12	34	23	19.5	16	14	230	5160
1159	3.5	34.5	12	38	27	23.5	20	18	220	5310
1164	4	14.5	12	18	6	2		6	220	2840
1166	4	18.5	12	22	10	6	2	6	220	3900
1167	4	22.5	12	26	14	10	6	8	220	4430
1168	4	26.5	12	30	18	14	10	12	220	4700
1168A	4	30.5	12	34	22	18	14	14	230	6040
1169	4	34.5	12	38	26	22	18	12	220	6100
1176	5	18.5	14	22	8	3		6	220	4300
1177	5	22.5	14	26	12	7	2	8	220	5400
1178	5	26.5	14	30	16	11	6	12	230	5580
1178A	5	30.5	14	34	20	15	10	12	230	6860
1179	5	34.5	14	38	24	19	14	12	220	7590
1187	6	22.5	14	26	10	4		6	230	6290
1188	6	26.5	14	30	14	8	2	8	230	6995
1188A	6	30.5	14	34	18	12	6	14	220	8050
1189	6	34.5	14	38	22	16	10	12	220	9110
1197	7	22.5	14	26	8	1		6	230	6930
1198	7	26.5	14	30	12	5		12	220	8160
1198A	7	30.5	14	34	16	9	2	14	230	9395
1199	7	34.5	14	38	20	13	6	12	220	10625