

## MARSHALL 1300 SERIES FURNACE

MODEL NUMBER	INTERNAL		EXTERNAL		FLAT ZONE @ 1000°C			TAPS	VOLTS	WATTS
	ID	LENGTH	OD	OAL	± 6°	± 3°	± 1°			
13 21	1.5	8.5	10	12.5	5.5	4.0	2.50	6	55	801
13 22	1.5	12	10	16.0	9.0	7.5	6.00	6	76	1131
13 24	1.5	16	10	20.0	13.0	11.5	10.00	8	99	1508
13 26	1.5	20	10	24.0	17.0	15.5	14.00	10	123	1885
13 27	1.5	24	10	28.0	21.0	19.5	18.00	12	146	2262
13 28	1.5	28	10	32.0	25.0	23.5	22.00	14	170	2684
13 29	1.5	32	10	36.0	29.0	27.5	26.00	14	193	3016
13 31	2	8.5	10	12.5	4.5	2.5	0.50	4	70	1008
13 32	2	12	10	16.0	8.0	6.0	4.00	6	104	1508
13 34	2	16	10	20.0	12.0	10.0	8.00	6	137	2011
13 36	2	20	10	24.0	16.0	14.0	12.00	10	163	2520
13 37	2	24	10	28.0	20.0	18.0	16.00	12	210	3016
13 38	2	28	10	32.0	24.0	22.0	20.00	14	233	3519
13 39	2	32	10	36.0	28.0	26.0	24.00	14	266	4021
13 41	2.5	8.5	10	12.5	3.5	1.0		5	97	1335
13 42	2.5	12	10	16.0	7.0	4.5	2.00	6	125	1884
13 44	2.5	16	10	20.0	11.0	8.5	6.00	8	172	2513
13 46	2.5	20	10	24.0	15.0	12.5	10.00	10	211	3142
13 47	2.5	24	10	28.0	19.0	16.5	14.00	12	250	3767
13 48	2.5	28	10	32.0	23.0	20.5	18.00	14	290	4398
13 49	2.5	32	10	36.0	27.0	24.5	22.00	14	330	5027
13 51	3	8.5	10	12.5	2.5			6	115	1602
13 52	3	12	10	16.0	6.0	3.0		6	180	2262
13 54	3	16	10	20.0	10.0	7.0	4.00	8	203	3016
13 56	3	20	10	24.0	14.0	11.0	8.00	10	250	3768
13 57	3	24	10	28.0	18.0	15.0	12.00	12	296	4524
13 58	3	28	10	32.0	22.0	19.0	16.00	14	343	5278
13 59	3	32	10	36.0	26.0	23.0	20.00	14	390	6032
13 61	3.5	8.5	12	12.5	1.5			6	129	1869
13 62	3.5	12	12	16.0	5.0	1.5		6	180	2639
13 64	3.5	16	12	20.0	9.0	5.5	2.00	8	228	3519
13 66	3.5	20	12	24.0	13.0	9.5	6.00	10	275	4398
13 67	3.5	24	12	28.0	17.0	13.5	10.00	12	348	5278
13 68	3.5	28	12	32.0	21.0	17.5	14.00	14	402	6157
13 72	4	12	14	16.0	4.0			6	204	3016
13 74	4	16	14	20.0	8.0	4.0		8	258	4021
13 76	4	20	14	24.0	12.0	8.0	4.00	10	334	5027
13 77	4	24	14	28.0	16.0	12.0	8.00	12	395	6032
13 84	5	16	14	20.0	6.0	1.0		8	345	5027
13 86	5	20	14	24.0	10.0	5.0		10	420	6283